



The .50in range drum (L8A1) has ballistic optimisation for the current range of in-service .50in. ammunition. The range drum is graduated from 500m to 2200m in 100m increments. It features a Gaseous Tritium Light Source (GTLS) for illumination of the range scale under conditions of low light level.

The rail for attachment of the optical sight is the Mil Std 1913 Picatinny type to suit the various natures of sighting system. There is a high degree of commonality between the various models and a full range of sub-assemblies and component parts are available where required to carry out a repair.

## Features include:

Picatinny rail grabber	The range drum is fitted with a quick release clamp that allows fitting to a Mil Std 1913 Picatinny rail.
Triple Picatinny rails	The range drum is fitted with a top mounted sight rail capable of taking Picatinny type sights, such as the ACOG or EoTech and 2 x side mounted Picatinny rails suitable for mounting lasers/torces etc.
Elevation lock	The mount features a rotary locking device fitted to the range adjusting drum, that when applied prevents inadvertent rotation.

## Technical Specification:

Part number	3649
Weight Total	1.65kg
Weapon fit	0.50" M2 HMG
Mounting Method	Picatinny rail grabber
Rail Qty / Type	3 x Mil Std 1913 Picatinny
Range	500m - 2200m
Elevation lock	Yes
L&A	L8A1
NSN	1240-99-453-6634